



## K8DT-LS1TD

Monitoring relay 17.5 mm wide, Conductive level control for liquid, 10k to 100k Ohm, 1 x Transistor, 24 V AC/DC

Application	Ordinary purified water, Sewage water
Functions	Conductive level control
Cable length	100 m
Installation type	DIN Rail
Terminal	Push-in
Size	17.5 mm
Supply voltage AC	20.4-26.4 V
Supply voltage DC	20.4-26.4 V
Output type	NPN
Body color	Black
Number of inputs for electrodes	3

## Aksesuarlar



**BF-1**

Electrode holder, 1-pole electrode, standard type (150°C), liquid with low specific resistance



**BF-3**

Electrode holder, 3 way, standard type (150°C)



**BF-5**



**BS-1**

Electrode holder, 1-pol electrode, for high pressure or high temperature applications (250°C), 1.96Mpa



**F03-11**

Protective cover for electrode holders PS or BF series)



**F03-12**

PS Electrode Holder Mounting Plate



**F03-14 1P**

Electrode separator, 1 electrode, ceramic, 250 °C max, 15 g



**F03-14 5P**

Electrode separator, 5 electrodes, ceramic, 250 °C max, 30 g

**F03-60 SUS316**

Set including F03-01 SUS316 electrode, F03-02 SUS316 connecting nuts, F03-03 SUS316 lock nuts

**PH-2 HAIPREN CODE 20M**

Underwater Electrode, Hypalon cable, double pole, 20 m length



**PS-31 SUS304 1000MM**

Electrode set, holder & electrodes, 1 m length, 4 mm diameter, non-extendable



**PS-31 SUS304 300MM**

Electrode set, holder & electrodes, 0.3 m length, 4 mm diameter, non-extendable



**PS-3S**

Electrode holder, 3 way



**PS-4S**

Electrode holder, 4 way



**PS-5S**

Electrode holder, 5 way



**Y92A-D1A**

Plastic cover for H3DT & K8DT

## CAD Kütüphanesi



### EAC Mark removal Üretimden Kaldırılma Bildirimi

EN PDF 221 KB



### K8DT-LS Conductive Level Controller Veri Sayfası

EN PDF 3,06 MB



### Panel Building Broşür

TR PDF 15,9 MB